Subject Index for
Electronics and Communications in Japan, Part I, Volume 75, 1992

16 QAM: **4**, 97-107
16-QAM signal: **5**, 85-97
3-D motion estimation: **8**, 64-75
3-D shape model: **8**, 64-75
620-Mbits/s switching: **6**, 1-13
99-percent bandwidth: **5**, 1-12
Absorption characteristics: **8**, 77-98
Access control scheme: **2**, 48-59
Access protocol: **9**, 69-80
Adaptive equalizer: **5**, 98-109
Adjacent channel selectivity: **12**, 87-96
Akima interpolation scheme: **7**, 93-100
ALOHA protocol: **1**, 11-23
Allan variance values: **11**, 59-71
Amplifier arrangement methods: **3**, 95-105
Angle of arrival: **4**, 108-116
Antennas: **11**, 80-88; 89-98
Antenna characteristics computation: **7**, 93-100
Antenna feeds: **7**, 101-115
Antenna generated radiation field: **2**, 104-116
Antenna impedance: **11**, 37-46
Array antenna: **3**, 106-114
Array exiting coefficients: **8**, 97-107
Associate memory-type neural network: **11**, 1-13
Asynchronous transfer mode (ATM): **5**, 23-33; **10**, 30-41; **11**, 27-36; **12**, 1-11
ATM control: **7**, 22-33
ATM network: **4**, 13-23
ATM network reliability: **4**, 86-96
ATM switch: **7**, 34-46; **6**, 14-2; **8**, 16-25
ATM switching network: **8**, 26-41
ATM transfer: **12**, 24-37
Atmospheric refractive index: **4**, 108-116
Autoclave: **8**, 77-98
Automatic generalization: **11**, 1-13
Automatic protection switch: **8**, 1-15
Averaging process: **10**, 42-54
B-ISDN: **8**, 26-41; **9**, 1-15
Balanced pair cable fault location: **3**, 52-61
Bandwidth: **6**, 97-106
Bandwidth allocation: **9**, 69-80
BER performance: **4**, 97-107
Bipolar transistor: **5**, 34-43
Blocking: **9**, 1-15
BPSK optical coherent communications: **1**, 69-81
Branch-and-bound technique: **8**, 54-63
Branching loss: **8**, 76-87
Bridge: **11**, 14-26
Buffered Banyan network: **7**, 34-46
Burst mode transmission: **2**, 60-70
Bus-type distribution: **8**, 76-87
CATV techniques: **7**, 1-12
Cable networks: **10**, 55-66
Cable replacement or recharging: **9**, 57-68
Call admission control: **4**, 13-23
Capture effect: **1**, 11-23
Carrier frequencies offset compensation: **5**, 98-109
Carrier-acquisition-during-training (CAT): **5**, 98-109
Cascade connection: **11**, 80-88
Cell discarding: **11**, 27-36
Cell loss: **10**, 30-41
Cell loss probability: **6**, 14-25; **8**, 16-25
Cell transfer control: **8**, 16-25
Cell transfer delay: **8**, 26-41
Cell-packing method: **5**, 23-33
Center measurement system: **7**, 1-12
Ceramic filter: **12**, 87-96
CHACLE: **7**, 80-92
CHILL: **6**, 26-40
Channel assignment: **4**, 24-36
Channel filter: **12**, 87-96
Channel group virtual circuit scheme: **1**, 1-10
Channel mismatch: **12**, 50-63
Chip interleaving: **4**, 46-58
Chirp radar: **9**, 81-88
Chirp transform: **9**, 81-88
Circuit-switching network: **8**, 1-15
Circular equation: **11**, 72-79
Class E resonant switch: **1**, 82-96
Co-channel interface power: **7**, 58-67
Code division multiplex system (CDM): **7**, 58-67
Code shift keying (CSK): **6**, 50-63
Coded modulation: **4**, 97-107
Coded video signals: **5**, 23-33
Coding: **10**, 67-78
Coherence: **2**, 38-47
Coherent detection technique: **10**, 42-54
Coherent OTDR: **12**, 76-86
Coherent optical communication systems: **11**, 99-107
Communication equipment for moving vehicles: **11**, 89-98
Communication network: **12**, 12-23
Communication service: **1**, 56-68
Communication satellite: **10**, 104-110
Communication systems: **5**, 13-22
Composite transmission: **2**, 60-70
Compression gain: **5**, 75-84
Computational quantity: **8**, 54-63

Concurrent object model: **6**, 26-40
Conformal array: **12**, 97-105
Congestion: **9**, 1-15
Connection loss: **3**, 21-32; **4**, 74-85
Content fuzzy retrieval: **11**, 1-13
Control algorithm: **7**, 22-33
Convolutional code: **5**, 1-12
Corporate communication network: **8**, 54-63
Corporate networks: **3**, 1-11
Correlation process: **10**, 42-54
Corrugation depth of horn antennas: **1**, 110-119
Cost lower bound: **3**, 1-11
CPFSK: **8**, 42-53
CPM: **5**, 1-12
Cross-correlation function: **6**, 41-49
CSMA/CD system: **2**, 24-37
Current distribution: **5**, 110-115
Current transformer: **5**, 34-43
Cycle slipping: **9**, 101-115
Cyclic code: **9**, 31-40
Cyclic multiqueue system: **6**, 14-25; **8**, 16-25
Data transmission on power lines: **4**, 46-58
Data-link protocol: **11**, 14-26
DC-DC converters: **1**, 82-96
Deep-space probe Ecliptic plane: **11**, 59-71
Degenerate sequence amplifier: **1**, 69-81
Delay: **11**, 27-36
Delay queueing system: **12**, 64-75
Demodulator: **5**, 75-84
Derouting: **9**, 1-15
Diakoptic method: **5**, 110-115
Dielectric-rod antenna: **2**, 104-116
Digital beam forming: **6**, 76-86
Digital cellular telephone system: **2**, 60-70
Digital communication network switching system: **3**, 41-51
Digital correlation processing: **3**, 72-84
Digital filters: **5**, 13-22
Digital mobile radio **5**, 98-109; **12**, 87-96
Digital phase locked loop: **4**, 1-12
Digital signal processing PLL: **3**, 12-20
Digital structures: **7**, 47-57
Diplexer: **7**, 101-115
Dipole array: **11**, 80-88
Direct sequence: **4**, 46-58, **5**, 75-84
Direct sequence-spread spectrum communications: **7**, 68-79
Discrete capacity: **8**, 54-63
Discrete cosine transform: **4**, 59-73
Disk-loaded monopole antenna: **5**, 110-115
Dispersion shifted optical fiber: **1**, 36-45
Dispersive media **6**, 87-96
Distance resolution: **3**, 72-84
Distributed call processing: **6**, 26-40
Distributed cooperative multiagent model: **12**, 24-37
Distributed multiagent model: **12**, 12-23
Distributing network: **9**, 1-15
Dither image: **9**, 42-56
Diversity: **6**, 107-117
Dividing method: **8**, 54-63
Document security: **7**, 47-57
Doppler frequency shift: **11**, 59-71
Doppler shift: **9**, 89-100
Doppler VOR (DVOR): **11**, 37-46
Down-link: **7**, 1-12
Earth station: **7**, 101-115; **8**, 99-107
Earth station transmitter: **2**, 71-81
ECD: **7**, 80-92
Economic networks: **3**, 1-11
Economical network design: **8**, 54-63
Effective reflection coefficient: **6**, 64-75
Electromagnetic field analysis: **6**, 87-96
Electromagnetic field distribution: **2**, 104-116
Electromagnetic shielding: **1**, 97-109
Electromagnetic wave law: **6**, 50-63
Electromagnetically coupled (EMC) dipole array: **3**, 106-114
Electronic enclosures: **1**, 97-109
Elliptical corrugated horn antennas: **1**, 110-119
Encryption: **7**, 47-57
End fire array: **11**, 80-88
End-to-end scheme: **7**, 13-21
End-to-end transfer delay: **12**, 38-49
Equalizer: **11**, 47-58
Er-doped optical filter: **12**, 76-86
Error recovery: **11**, 14-26
Error-correction codes: **9**, 31-40
Euclidean distance: **5**, 1-12
Expandability: **8**, 26-41
Facsimile: **9**, 42-56
Facsimile mail: **7**, 47-57
Fading compensation: **4**, 97-107
Fading reduction: **4**, 108-116
Failure probability: **10**, 15-29
Fast algorithm: **4**, 59-73
Fast Fourier transform: **3**, 72-84
Fault location: **3**, 52-61
Fault location in paired cables: **1**, 46-55
FD-TD method: **6**, 87-96
Feed array: **8**, 99-107
Fiber lateral vibration: **9**, 57-68
Fiber longitudinal vibration: **9**, 57-68
Fiber transfer splicing: **9**, 57-68
Fiber-optic network: **8**, 1-15
Field experiment: **8**, 42-53
Field leakage suppression: **1**, 97-109
Finite difference time domain method: **6**, 87-96
Finite-source delay: **12**, 64-75
Five-viewpoint model: **12**, 24-37
Flow deviation: **3**, 1-11

Forward voltage diode: **5**, 34-43
Free access network: **12**, 50-63
Frequency analysis/synthesis: **4**, 59-73
Frequency occupancy bandwidth: **5**, 13-22
Frequency selective fading: **9**, 89-100
Frequency-dependent material: **6**, 87-96
Frequency-modulated continuous wave (FM-CW) radar: **3**, 85-94
Functional assignment: **10**, 55-66
Generalized Geffe sequence: **6**, 41-49
Generating mechanism: **11**, 37-46
Global optimization: **5**, 44-53
Gravity compensation: **10**, 79-88
Gravity distortion: **7**, 93-100
Gray-scale images: **9**, 42-56
Hardware scale: **8**, 26-41
Harmonic-controlled type: **10**, 89-103
HDLC: **11**, 14-26
Helical traveling-wave tube (TWT): **2**, 60-70
Heterodyne detection: **8**, 42-53
Heuristic algorithm: **3**, 1-11
High definition television (HDTV): **10**, 67-78
High definition video signal: **2**, 11-23
High dynamic range: **12**, 76-86
High power amplifier (HPA) arrays: **3**, 95-105
High resolution object detection: **3**, 85-94
High-permeability sheet: **1**, 97-109
High-precision antenna directivity: **2**, 94-103
High-speed communication networks: **1**, 1-10
High-speed ring network: **2**, 48-59
Hilbert transformer: **5**, 13-22
Human body modeling: **3**, 62-71
Image compression: **9**, 42-56
Image data compression: **4**, 59-73
Image storage: **9**, 42-56
Image transmission: **9**, 42-56
Impulsive burst noise: **4**, 46-58
Index matching material: **4**, 74-85
Inductive inference reasoning: **11**, 1-13
Inherent bearing error: **11**, 37-46
Input impedance: **5**, 110-115; **6**, 97-106
Input-admittance measurement fault location: **3**, 52-61
Integrated service digital network: **12**, 1-11
Integrated service graph (ISG): **1**, 56-68
Intelligent network: **11**, 1-13
Intelligent telecommunication network: **12**, 24-37
Interference cancelers: **5**, 85-97
Interference cancellation: **5**, 85-97; **6**, 107-117
Internal event: **9**, 16-30
Interruption: **9**, 101-115
Intersymbol interference: **12**, 87-96
ISDN basic service: **9**, 101-115
ISM band: **5**, 62-74
Isolation improvement among output ports: **3**, 95-105
Jig: **10**, 79-88
Land mobile communication: **2**, 60-70; **9**, 89-100
Lapped orthogonal transform: **4**, 59-73
Laser diode phase noise: **2**, 94-103
Lattice-type: **8**, 26-41
LBG algorithm: **2**, 1-10
Least-squares combining: **6**, 107-117
Limited transmission CSMA/CD system: **2**, 24-37
Line-of-sight propagation: **6**, 64-75
Linear distortion compensation: **11**, 47-58
Link-by-link scheme: **7**, 13-21
Local area network: **9**, 69-80
Loran: **7**, 80-92
Low frequency jitter: **4**, 1-12
Low intermodulation: **10**, 89-103
Low-voltage power supply: **5**, 34-43
MAN: **9**, 1-15
Majority logic combination sequence: **6**, 41-49
Manchester coded PN sequence: **7**, 68-79
Master-slave synchronization system: **3**, 12-20
Matched channel reservation: **12**, 50-63
Matched filter: **5**, 75-84
Matching post: **5**, 110-115
Matrix-analytic method: **4**, 37-45
Maximal ratio: **6**, 107-117
Maximum likelihood estimation: **4**, 97-107
Maximum-likelihood decoding algorithm: **9**, 31-40
Mean waiting time: **8**, 16-25
Measurement: **8**, 108-117
Medium attachment unit: **7**, 1-12
Mesh reflector antenna: **10**, 104-110
Metallic cylinder: **8**, 77-98
Microstrip antenna: **6**, 76-86; **6**, 97-106; **12**, 97-105
Microstrip dipole array coupling: **3**, 106-114
Microwave components: **7**, 101-115
Microwave fading: **6**, 64-75
Military communication: **5**, 54-61
Mismatch probability: **12**, 50-63
Mobile communication: **5**, 54-61
Mobile communication equipment: **10**, 104-110
Mobile communications satellite: **10**, 89-103
Mobile satellite communication: **6**, 76-86; **11**, 89-98; **12**, 97-105
Modal noise: **2**, 38-47
Mode dispersion: **2**, 38-47
Mode matching method analysis: **8**, 108-117
Model-based image coding: **8**, 64-75
Modem design: **9**, 101-115
Moment method: **5**, 110-115
Monopulse horn antenna: **2**, 82-93
Monopulse pattern-forming method: **2**, 82-93
Moving facial images: **8**, 64-75
MS synchronization networks: **3**, 12-20
Multi-link failure restoration: **4**, 86-96
Multibeam antenna configurations: **2**, 82-93
Multichannel packet network: **1**, 1-10

Multidimensional traffic model: **12**, 64-75
Multielectrode DFB-LD: **8**, 42-53
Multimedia integrated communication network: **4**, 13-23
Multimedia multiplexing: **7**, 22-33
Multimedia traffic: **4**, 13-23
Multipath allocation algorithm: **12**, 12-23
Multiple echo: **3**, 72-84
Multiplexing method: **7**, 22-33
Multiplexing performance: **7**, 22-33
Multiport amplifier (MPA): **3**, 95-105
Multisignature system: **7**, 47-57
Multistage switching network: **7**, 34-46
Multivalue sequence: **3**, 72-84
Multivendor telecommunication system: **5**, 44-53
Mutual coupling: **11**, 37-46
Mutual coupling of dipole arrays: **3**, 106-114
N-stage frequency divider: **4**, 1-12
Network architecture: **5**, 44-53; **12**, 1-11
Neural network: **4**, 24-36
Noninvasive electromagnetic hyperthermia: **3**, 62-71
Numerical analysis: **8**, 108-117
Numerical method: **6**, 87-96
Nyquist transmission: **12**, 87-96
OAM application architecture: **5**, 44-53
Object detection: **3**, 85-94
Object oriented programming: **6**, 26-40
Occultation: **11**, 59-71
Off-focus RF sensor: **2**, 82-93
On-board antenna: **7**, 93-100
Operation-maintenance: **10**, 55-66
Optical accessing: **3**, 33-41
Optical fiber: **1**, 36-45; **8**, 76-87
Optical fiber amplifier: **12**, 76-86
Optical fiber cable transfer: **10**, 15-29
Optical fiber cables rerouting: **3**, 21-32
Optical fiber communication system: **3**, 41-51
Optical fiber connector: **10**, 15-29
Optical fiber core illumination technique: **3**, 33-41
Optical fiber fault location: **3**, 52-61
Optical fiber outside plants: **1**, 24-35
Optical fiber switch: **3**, 41-51
Optical heterodyne spatial tracking system: **2**, 94-103
Optical intersatellite communication: **2**, 94-103
Optical multifiber connector: **3**, 21-32
Optical orthogonal code: **6**, 41-49
Optical subscriber network: **10**, 55-66
Optical theorem Poynting vector: **11**, 72-79
Optical transfer splicing: **3**, 21-32; **4**, 74-85
Optical transmission: **2**, 38-47
Optical/electrical converter: **8**, 108-117
Optimum vector quantizers: **2**, 1-10
Orientation polarization: **6**, 87-96
Orthogonal sequences: **7**, 58-67
OSI directory: **10**, 1-14
OTDR: **10**, 42-54; **12**, 76-86
Overlapping block transform: **4**, 59-73
Packaging system: **6**, 1-13
Packet switch architecture: **1**, 1-10
Packet switching: **1**, 1-10; **1**, 11-23; **7**, 13-21; **12**, 1-11
Packet-switching network: **8**, 1-15; **12**, 38-49
Paired subscriber cables: **1**, 46-55
Partial response: **5**, 1-12
Passive reflector: **4**, 108-116
Peak power multiplication ratio: **9**, 81-88
Performance analysis: **12**, 38-49
Performance deterioration: **8**, 1-15
Performance evaluation: **11**, 14-26
Periodic burst noise: **4**, 46-58
Petri nets: **1**, 56-68
Phase jitter: **9**, 101-115
Phase noise: **11**, 99-107
Phase noise cancellation: **11**, 99-107
Phase shift keying (PSK): **9**, 101-115
Phase type Markov renewal process (PH-M RP): **4**, 37-45
Phase-type (PH) distribution: **4**, 37-45
Phased array: **6**, 76-86
Photogrammetry: **10**, 79-88
Photonic switching: **8**, 26-41
Picture quality: **10**, 30-41
Planar antenna: **5**, 110-115
Planar inverted-F antenna: **6**, 97-106
Planar-type absorbers: **8**, 77-98
Plant management for communication cables: **1**, 24-35
Polarization diversity: **8**, 42-53
Polarization modulation system: **11**, 99-107
Policing control: **4**, 13-23
Polling control: **7**, 22-33
Power control during transmission (PCT): **1**, 11-23
Power loss distribution in modeling: **3**, 62-71
Powerline data transmission: **7**, 68-79
Preamble: **9**, 101-115
Prediction method: **11**, 37-46
Prepreg: **8**, 77-98
Prioritized resolvable-contention-ring access: **2**, 48-59
Priority control: **8**, 16-25
Priority mechanism: **2**, 48-59
Process expansion: **9**, 16-30
Propagation time delay: **7**, 80-92
Protocol validation: **9**, 16-30
Pulse compression ratio: **9**, 81-88
Pulse compression sonar: **3**, 72-84
Pulse echo fault location: **1**, 46-55
Pulse waveform distortion: **7**, 80-92
PWM switch alternative: **1**, 82-96
QPSK: **12**, 87-96
Quadrature demodulation: **11**, 47-58
Quadrature modulation: **11**, 47-58

Quality control: **11**, 27-36
Quantum communication: **1**, 69-81
Quasi-birth-and-death (QBD) process: **4**, 37-45
Quasi-random input: **12**, 64-75
Queueing control: **7**, 22-33
Rack system: **6**, 1-13
Radiation characteristics: **8**, 108-117
Radiation pattern: **4**, 108-116
Radio: **6**, 107-117
Radio meteorology: **6**, 64-75
Radio system: **5**, 54-61
Radio transmission: **11**, 47-58
Radio wave propagation: **11**, 89-98
Raised-cosine pulse: **7**, 58-67
Rayleigh fading: **4**, 97-107
Reachability analysis: **9**, 16-30
Reachability tree: **9**, 16-30
Real value orthogonal PN sequence: **3**, 72-84
Realtime management system: **1**, 24-35
Rearrangement: **4**, 24-36
Rectangular pulse: **7**, 58-67
Reference model: **5**, 44-53
Reference PN sequence: **7**, 68-79
Reinjection-type interference canceler: **5**, 85-97
Reliability: **8**, 26-41; **9**, 1-15
Reliable networks: **3**, 1-11
Rerouting optical fiber cables: **4**, 74-85
Resonance equation: **6**, 97-106
Resonant switch characteristics: **1**, 82-96
Resonant switch topologies: **1**, 82-96
Retiming methods: **6**, 1-13
Retransmission algorithm: **2**, 24-37
Ridged waveguides: **7**, 101-115
Ring network: **9**, 69-80
Robustness: **11**, 1-13
Rotary mechanical optical fiber switch: **3**, 41-51
Rotational transfer response time: **3**, 41-51
Route associate buffer: **6**, 14-25
Route selection control: **8**, 1-15
Routing: **9**, 1-15
SAW convolver: **5**, 62-74
SAW device: **5**, 62-74; **5**, 75-84
Satellite broadcasting: **1**, 110-119
Satellite communication: **2**, 60-70; **7**, 101-115
Satellite navigation system: **11**, 89-98
Satellite TDMA system: **9**, 81-88
Satellite-borne antenna: **10**, 79-88; **2**, 82-93
Satellites: **8**, 99-107
Scattering cross section: **11**, 72-79
Selective circuits: **12**, 50-63
Self-healing algorithms: **4**, 86-96
Self-pulsation laser diode: **2**, 38-47
Self-routing: **8**, 26-41
Sequence inversion keying: **6**, 50-63
Service example learning: **11**, 1-13
Service scenario: **6**, 26-40
Shape change detection: **8**, 64-75
Shaped beam antenna: **1**, 110-119; **8**, 99-107
Short-time DFT: **5**, 13-22
Sidelobe level: **10**, 104-110
Signal multiplexing: **2**, 11-23
Signal synchronization: **2**, 11-23
Simulated annealing algorithm: **2**, 1-10
Single-mode multifiber connector: **4**, 74-85
Single-mode optical fiber connectors: **3**, 33-41
Single-pulse transmission mode: **9**, 81-88
Small antenna: **5**, 110-115; **6**, 97-106
Solid-state power amplifier: **10**, 89-103
Space correlation coefficient: **6**, 64-75
Space diversity: **6**, 64-75
Spatial network method: **6**, 97-106
Spectral efficiency: **6**, 41-49
Spherical array: **12**, 97-105
Spherical array antenna: **6**, 76-86
Spherical dipole antenna: **8**, 108-117
Spread spectrum (SS) communication: **6**, 50-63
Spread spectrum Code division: **5**, 54-61
Spread spectrum communication: **3**, 72-84; **5**, 62-74
Spread spectrum communication system: **4**, 46-58; **6**, 41-49
Spread spectrum multiple access (SSMA): **6**, 41-49
Spread time spread spectrum: **4**, 46-58
Spreading code: **6**, 41-49
Squeezing properties: **1**, 69-81
Steepest gradient method: **9**, 89-100
Stokes parameters: **11**, 72-79
Structural mathematical model: **10**, 79-88
Structured packing: **5**, 23-33
Stuffing synchronization system: **4**, 1-12
Subband: **10**, 67-78
Subband/transform coding: **4**, 59-73
Subjective quality: **10**, 30-41
Subscriber network: **1**, 36-45; **10**, 42-54
Superdirectivity: **11**, 80-88
Switching equipment: **6**, 1-13
Switching network: **9**, 1-15
Synchronization: **7**, 68-79
Synchronization control method: **10**, 15-29; **6**, 50-63
Synchronization tracking: **6**, 50-63
Synchronous detection: **10**, 42-54
Synchronous rectifier: **5**, 34-43
Synthetic aperture FM-CW radar: **3**, 85-94
Tandem queueing network: **7**, 13-21; **12**, 38-49
TDMA circuit switching: **7**, 1-12
Telecommunication networks: **1**, 36-45
Telecommunications networks: **5**, 44-53
Telephone delivery service: **11**, 1-13
Thermal deformation: **10**, 79-88
Thermal distortion: **7**, 93-100
Three-ray model: **6**, 64-75

Throughput analysis: **11**, 14-26
Time-slotted bus system: **7**, 1-12
Time-token control scheme: **2**, 48-59
Timeout retransmission: **7**, 13-21
Timer process: **9**, 16-30
Topological design: **3**, 1-11; **8**, 54-63
Total service graph (TSG): **1**, 56-68
Traffic analysis: **6**, 14-25
Traffic between nodes: **12**, 50-63
Traffic integration: **9**, 69-80
Train: **9**, 69-80
Transfer splicing mechanism: **3**, 21-32; **4**, 74-85
Transform coding: **4**, 59-73
Transformation format: **9**, 101-115
Transmission in broadband ISDN: **2**, 11-23
Transmission system: **5**, 54-61
Transponder: **9**, 81-88
Tree-type distribution: **8**, 76-87
Trellis-coded 16-QAM/TDMA system: **2**, 60-70
Triangle networks: **3**, 1-11
Trunk line: **10**, 15-29
Trunk transmission line: **1**, 36-45
Two-branch diversity reception: **6**, 107-117
Two-mode fiber: **2**, 38-47
Two-valued sequence: **3**, 72-84
Unique word: **9**, 101-115
UPT: **10**, 1-14
UPT name server: **10**, 1-14
Up-link: **7**, 1-12
User programmability of communication networks: **11**, 1-13
Variable control: **7**, 1-12
Variable transmission rate: **9**, 101-115
Variable-amplitude circuit: **5**, 85-97
Variable-phase circuit: **5**, 85-97
Vector quantization: **2**, 1-10
Velocity dispersion characteristics of antennas: **1**, 110-119
Video communication: **10**, 30-41
Video transmission: **10**, 67-78
Virtual path concept: **4**, 86-96
Wave absorbers: **8**, 77-98
Wave bending: **4**, 108-116
Wave environment: **9**, 89-100
Waveform pattern matching: **1**, 46-55
Window flow control: **11**, 14-26
Wired transmission line antenna: **6**, 97-106
Wireless LAN: **5**, 62-74
Z-channel: **9**, 31-40